



418.3267

BASE EMPOTRABLE

32A 3P+N+T 6h 346-415V 50Hz 60Hz
84X106MM Bornes con tornillo

Product Approvals

| TECHDATA | | STANDARDS AND LAWS | |
|------------------------------|---------------------|-----------------------------------|---|
| Tipo de producto | BASE EMPOTRABLE | EN 60309-1 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Serie comercial | Serie OPTIMA | EN 60309-2 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Descripción | BASE EMPOTRABLE | | |
| Intensidad nominal | 32A | | |
| Polos | 3P+N+T | EN 60309-1/A1 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Posición de hora | 6h | EN 60309-2/A1 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Tensión nominal (range) | 250-400V | | |
| Tensión nominal | 346-415V | EN 60309-1/A2 (2012) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Frecuencia nominal | 60Hz | | |
| Frecuencia nominal | 50Hz | EN 60309-2/A2 (2012) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Color | ROJO | | |
| Material | TERMOPLÁSTICO | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Grado de protección | Watertight | | |
| Grado de protección IP | IP66/IP67/IP69 | | |
| Grado de protección IK | IK08 | | |
| Tipos de salidas disponibles | INCLINADA | | |
| Bornes | Bornes con tornillo | | |
| Material de los contactos | CuZn (latón) | | |

Brida de fijación

84X106MM